

BHB Hydraulic Breakers




BHB Range
Hydraulic
Road Breakers



No.1 for Light Construction Equipment

www.ALTRAD-Belle.com



- » **NEW** improved, lock-on, ergonomic handgrips
- » Compatible with the range of ALTRAD Belle Hydraulic Power Packs.
- » Frequency and Blow Rates to achieve maximum productivity.
- » For use on a number of materials, from light brickwork to asphalt.
- » Delivered with 1/2" tail-hoses with 1/2" flat-face couplings.
- » Hoses are removable for easy transportation and storage. Can also be changed quickly if damaged.
- » Very reliable and simple to maintain = less servicing costs.



Compatible with Altrad Belle HPP Power Packs

Technical Specifications

Model	BHB 12 (Part No. BHB12S)	
Max Pressure	(bar)	160
Hydraulic Flowrate	(l/min)	20
Blows per Minute		2400
3-Axis Vibration	(m/sec ²)	**16.08
Breaking Force	(J)	25
Steel Size	(mm)	22 x 82
Weight	(kg)	14

Model	BHB 23 (BHB23S)	
Hydraulic Flowrate	(l/min)	160
Flow	(l/min)	20
Blows per Minute		1600
3-Axis Vibration	(m/sec ²)	**11.97
Breaking Force	(Joules)	65
Steel Size	(mm)	25 x 108
Weight	(kg)	23.5

Model	BHB 25 (BHB25S)	
Max Pressure	(bar)	160
Hydraulic Flowrate	(l/min)	20
Blows per Minute		1300
3-Axis Vibration	(m/sec ²)	**11.1
Breaking Force	(Joules)	85
Steel Size	(mm)	32 x 160
Weight	(kg)	28

Model	BHB 25X (BHB25XS)	
Max Pressure	(bar)	160
Hydraulic Flowrate	(l/min)	20
Blows per Minute		1600
3-Axis Vibration	(m/sec ²)	**6.5
Breaking Force	(Joules)	55
Steel Size	(mm)	32 x 160
Weight	(kg)	25



Range of Steels available including a Rammer Steel Option.

Model	BHB 27 (BHB27S)	
Max Pressure	(bar)	160
Hydraulic Flowrate	(l/min)	*20/30
Blows per Minute		1300 (20ltr)
Blows per Minute		2150 (20ltr)
3-Axis Vibration	(m/sec ²)	**11.8 (20ltr)
3-Axis Vibration	(m/sec ²)	**18.6 (30ltr)
Breaking Force	(Joules)	85
Steel Size	(mm)	32 x 160
Weight	(kg)	27

Model	BHB 27X (BHB27XS)	
Max Pressure	(bar)	160
Hydraulic Flowrate	(l/min)	*20/30
Blows per Minute		1300 (20ltr)
Blows per Minute		2150 (20ltr)
3-Axis Vibration	(m/sec ²)	**8.2 (20ltr)
3-Axis Vibration	(m/sec ²)	**6.8 (30ltr)
Breaking Force	(Joules)	85
Steel Size	(mm)	32 x 160
Weight	(kg)	30

* NOTE: - Breaker is supplied with alternative return pipe restrictors. Please ensure correct restrictor is fitted for 20 (3.4mm Restrictor) or 30 (Open Restrictor) Litre supply. (Restrictor size is marked on the restrictor body)
NO MARKINGS = OPEN RESTRICTOR

** OPERC Independent testing Vibration levels tested to BS28927-10

Dealer Stamp:

ALTRAD Belle Head Office, Sheen, Nr. Buxton, Derbyshire, SK17 0EU
 Tel: (+44) 01298 84606 Fax: (+44) 01298 84722 Email: sales@belle-group.co.uk
www.ALTRAD-Belle.com

Belle Group reserve the right to amend or improve any specifications in this brochure without notice.