

TDX

650A



TDX 650A
*Lightweight, Twin Drum,
 Walk Behind Rollers*



No.1 for Light Construction Equipment

www.ALTRAD-Belle.com

ALTRAD... BELLE... BarOmix... FORT... Limex... Richard Fraisse...



COMPACTING... MIXING... CONCRETING... CUTTING... BREAKING... MOVING... WHEELBARROWS

- » Highly responsive, low-maintenance Hydrostatic drive system.
- » High-powered, reliable, 10hp Air-Cooled, Electric Start Yanmar Diesel engine or 6.9hp Water Cooled Electric Start Kubota EA330 engine.
- » 16kN high compaction force for productivity
- » Recoil Start back-up on Yanmar engine.
- » High-quality Hydraulic System components.
- » 65 litre Water Tank with external gauge.
- » Wall clearance on both sides with no overhang.
- » Self-cleaning, adjustable Scraper Bars.
- » 18 litre Hydraulic Oil Tank.
- » Easy access, removable, front and rear anti-corrosive water sprinkler system.
- » Foldable handle with locking mechanism.
- » Easy to service - Remote Oil Drain.
Remote Oil Fill.
Air Cleaner Access.
- » Drain on Water Tank to prevent frost damage.
- » Centrally located Lifting Eye and 4 x Strapping/ Lifting Points.
- » Key Switch protection.
- » 2-layer factory powder coated components.
- » Customer colour options available.
- » Optional Hourmeter available.



6.9hp Kubota Engine Option



65ltr Water Tank with External Gauge

Technical Specifications

Model	TD X 650A Yanmar		Model	TD X 650A Kubota	
Width	(mm)	703	Width	(mm)	703
Drum Width	(mm)	650	Drum Width	(mm)	650
Length	(mm)	2318	Length	(mm)	2318
Height	(mm)	1137	Height	(mm)	1137
Engine Type		Yanmar L100N	Engine Type		Kubota EA330
Engine Power	(Hp/kW)	10 - 7.4	Engine Power	(Hp/kW)	6.9 - 5.2
Fuel Type		Diesel	Fuel Type		Diesel
Starting System		Electric (with Recoil Back-up)	Starting System		Electric
Water Tank Capacity	(Ltr)	65	Water Tank Capacity	(Ltr)	65
Oil Tank Capacity	(Ltr)	16	Oil Tank Capacity	(Ltr)	16
Forward Speed	(km/hr)	> 3.9	Forward Speed	(km/hr)	> 3.9
Reverse Speed	(km/hr)	> 2.1	Reverse Speed	(km/hr)	> 2.1
Centrifugal Force	(kN)	16	Centrifugal Force	(kN)	16
Vibration Frequency	(vpm)	3300	Vibration Frequency	(vpm)	3300
Weight	(kg)	675	Weight	(kg)	684
Noise Level	(dB(A))	107	Noise Level	(dB(A))	107

ALTRAD Belle Head Office, Sheen, Nr. Buxton, Derbyshire, SK17 0EU
 Tel: (+44) 01298 84606 Fax: (+44) 01298 84722 Email: sales@belle-group.co.uk

www.ALTRAD-Belle.com

Belle Group reserve the right to amend or improve any specifications in this brochure without notice.